HOOVER TREATED WOOD PRODUCTS, INC

TECHNICAL NOTE

FOR ADDITIONAL INFORMATION: www.frtw.com or 1-800-TEC-WOOD (832-9663)

DUAL TREATMENT Fire-Retardant & Preservative Together

Currently, there is <u>no</u> single treatment available that provides both exterior fire-retardant and preservative protection for wood products.

Dual treatment is sometimes suggested as a means of providing both properties; however, dual-treated wood cannot be certified as either fire-retardant or preservative treated. No Underwriters Laboratories or other fire-retardant flamespread classification mark can be applied, and no preservative identification mark can be applied to dual-treated wood. Without third party certification, dual treatment will not meet the Building Code requirements for either fire-retardant treatment or preservative treatment.

Dual treatment would require pressure treatment and kiln drying twice, the effects of which on design values or other properties are unknown at this time.

Naturally durable species such as redwood or western red cedar treated with *Exterior Fire X*® have been substituted for above ground applications calling for "dual treatment". *Pyro-Guard*® *plus* is available for interior, dry in service, weather protected applications where decay or termites may be of concern. Both products are code compliant where fire retardant treated wood is allowed by the building codes.

For information on *Exterior Fire X*®, *Pyro-Guard*® *plus* or other Hoover Treated Wood products, go to www.frtw.com or call 1-800-531-5558.