

# HOOVER TREATED WOOD PRODUCTS, INC.

## TECHNICAL NOTE

FOR ADDITIONAL INFORMATION: [www.frtw.com](http://www.frtw.com) or 1-800-TEC-WOOD (832-9663)

### ***PYRO-GUARD*<sup>®</sup> STORAGE, HANDLING AND INSTALLATION RECOMMENDATIONS**

*PYRO-GUARD*<sup>®</sup> interior fire retardant treated wood is recommended for use in interior applications (including roof, wall, and floor sheathing) and should not be used where it will be exposed to in-service weather, dampness, high humidity or wetting.

*EXTERIOR FIRE-X*<sup>®</sup> fire retardant treated wood is recommended for such high moisture applications.

#### **JOB SITE STORAGE**

As with untreated wood, exposure to rain, dampness and humidity can result in elevated moisture content. *PYRO-GUARD*<sup>®</sup> fire retardant treated wood must be kept dry prior to installation by such means as covering bundles with weather resistant materials, storing under shelter, elevating bundles to prevent ground contact, and allowing for air circulation around the wood.

If not immediately covered with felt, roofing or other weather barriers during installation, fire retardant treated wood exposed to the weather must be protected with temporary weather resistant covering. If wetted during construction, redry to 15% moisture content or replace before enclosure. These recommendations are consistent with those for untreated plywood from APA - The Engineered Wood Association.

#### **VENTILATION, MOISTURE AND HEAT**

Adequate air flow is needed across at least one surface in wood roof systems to control moisture and reduce temperature. This requires that ventilation be balanced and uniform. Enclosed cavities under flat or vaulted roofs are particularly hard to ventilate and require careful attention to detail to assure adequate ventilation. Minimum air flow requirements are prescribed by the building codes.

#### **CUTTING, MILLING OR SURFACING**

For *PYRO-GUARD*<sup>®</sup> lumber, milling or ripping parallel to grain should be done prior to treatment. Field cuts across the grain are permitted after treatment without field treatment of cut ends. *PYRO-GUARD*<sup>®</sup> plywood may be cut or ripped in any direction.

#### **FASTENERS**

Galvanized fasteners have been recommended for many years for all types of treated wood. *PYRO-GUARD*<sup>®</sup> is safe to use with galvanized nails, truss plates, duct work, plumbing, conduit and copper.

DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY HOOVER TREATED WOOD PRODUCTS, INC.: The information contained herein is true and accurate to the best of our knowledge, but is provided without warranty or guarantee. Since the conditions of use are beyond our control, Hoover Treated Wood Products, Inc. ("Hoover") disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein.