

BUGV.R7003 - Treated Plywood

Treated Plywood

See General Information for Treated Plywood

HOOVER TREATED WOOD PRODUCTS INC

154 WIRE RD
THOMSON, GA 30824-7988 USA

Plywood, impregnated by pressure process to reduce combustibility.

R7003

Pyro Guard, Pyro Guard Plus, and Pyro Guard Plus F

Specie Type or Grade	Flame Spread	Smoke Developed	Adjunct Statement
Southern Yellow Pine	15	30	B, C, F, G
Douglas Fir	FR-S	FR-S	C, F, G
Lauan	FR-S	FR-S	C, F, G
Note: Plywood in form of sheet, planks, beams or trusses, impregnated by pressure process to reduce combustibility.			
Master Plank	FR-S	FR-S	C & G
Kerto	FR-S	FR-S	C & G

Exterior Fire X, Type II

Specie Type or Grade	Flame Spread	Smoke Developed	Adjunct Statement
Douglas Fir	10	35	A, B, E, G
Southern Yellow Pine	15	50	A, B, E, G
Note: Plywood in form of sheet, planks, or trusses, impregnated by pressure process to reduce combustibility.			
Southern Yellow Pine Micro-Lam	FR-S	FR-S	A, E, G
Douglas Fir Mico-Lam, Red Plank	FR-S	FR-S	A, E, G
Spruce Master Plank	FR-S	FR-S	A, E, G
Southern Yellow Pine Gang-Lam	5	5-50	A, E, G

Pro Tex

Specie Type or Grade	Flame Spread	Smoke Developed	Adjunct Statement
Southern Yellow Pine	10	40-75	B, C, F, G
Douglas Fir	10	25-50	B, C, F, G
Lauan	10	25	—

Last Updated on 2019-10-15

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

BUGV.GuideInfo - Treated Plywood

[Building Materials] (Surface-burning Characteristics) (Plywood) Treated Plywood

See General Information for Plywood

GENERAL

This category covers the surface-burning characteristics of plywood treated by pressure impregnation to reduce combustibility, and plywood consisting of treated cores with treated or untreated face veneers that may or may not be prefinished.

In some cases, the designation "FR-S" appears in the individual certifications in place of the flame-spread and smoke-developed values. This designation denotes that the flame-spread and smoke-developed values applicable to a particular species or type of treated plywood are 25 or less and that the species or type has been subjected to tests of 30 min duration during which the flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners, with no evidence of significant progressive combustion.

Unless otherwise indicated, the treatments consist of water-soluble salts which will be affected by repeated exposure to water or conditions that may result in condensation. In order to determine the effect of moisture conditions on the surface-burning characteristics, treated plywood (where indicated in the individual certifications) has been subjected to a Standard Rain Test consisting of cyclic wetting and drying periods per ASTM D2898 (1994), "Standard Test Methods for Accelerated Weathering of Fire-Retardant-Treated Wood for Fire Testing." These products are eligible to bear the supplemental statement "No increase in the listed Classification when subjected to the Standard Rain Test, ASTM D2898-94."

Some species of treated plywood, as indicated in the individual certifications, have also been tested for spread of flame and evidence of significant progressive combustion for test of 30 min duration under the same conditions of exposure. These products are eligible to bear the supplemental statement "In test of 30 min duration, the flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners, with no evidence of significant progressive combustion."

In addition to the surface-burning characteristics, as indicated in the individual certifications, treated plywood conforming to AWPA C27 (1993), "Plywood - Fire-Retardant Treatment by Pressure Processes," may be provided. This standard contains specifications relating to moisture content, flame spread and hygroscopicity for "Interior Type A" performance ratings, moisture content, and flame spread and standard rain test for "Exterior Type" performance ratings.

Some species of treated plywood, as indicated in the individual certifications, have been tested in accordance with ASTM D3201 (1994), "Standard Test Method for Hygroscopic Properties of Fire-Retardant Wood and Wood-Base Products". These species of plywood are eligible to bear the supplement statement "Equilibrium moisture content of less than 28 percent when tested in accordance with ASTM D3201-1994 at 92 percent relative humidity."

Some species of treated plywood, as indicated in the individual certifications, have been kiln dried after treatment per ASTM D4442, "Standard Test Methods for Direct Moisture Content Measurement of Wood and Wood-Base Materials"/ASTM D4444 (1992), "Standard Test Methods for Use and Calibration of Hand-Held Moisture Meters." These species of plywood are eligible to bear the supplement statement "Kiln dried after treatment to a maximum moisture content of 15 percent in accordance with ASTM D4442/D4444-92."

Some treated plywood is provided with facings that may effect the contribution of combustibles under fire conditions. This effect is determined by testing the sample with a longitudinal butt joint, constructed by slitting the facing or by using a factory or field joint (if applicable).

One or more of the following adjunct statements, referenced above, may be indicated on the individual certifications by alphabetical letters having the following meanings:

A - No increase in the listed Classification when subjected to the Standard Rain Test, ASTM D2898-94.

B - In test of 30 min duration, flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners and there was no evidence of significant progressive combustion.

C - In accordance with AWPA C27-1993, Interior Type A.

E - In accordance with AWPA C27-93, Exterior Type.

F - Equilibrium moisture content less than 28% when tested in accordance with ASTM D3201-94 at 92% relative humidity.

G - Kiln dried after treatment to a maximum moisture content of 15% in accordance with ASTM D4442/ASTM D4444-1992.

The certifications are confined to the materials themselves and do not pertain to the structures in which the materials may be installed.

The structural qualities of this plywood have not been determined.

The toxicity of the products of combustion and other properties have not been investigated.

Authorities Having Jurisdiction should be consulted before installation.

PRODUCT IDENTITY

The following product identity appears on the product:

Treated Plywood

ADDITIONAL INFORMATION

For additional information, see Surface-burning Characteristics (BIKT) and Building Materials (AABM).

REQUIREMENTS

The basic standard used to investigate products in this category is ANSI/UL 723, "Test for Surface Burning Characteristics of Building Materials."

UL MARK

The Certification Mark of UL on the product is the only method provided by UL to identify products manufactured under its Certification and Follow-Up Service. The Certification Mark for these products includes the UL symbol, the words "CERTIFIED" and "SAFETY," the geographic identifier(s), and a file number.

Additional Certification Markings

Products covered under this category are additionally marked with the following information:

AS TO SURFACE-BURNING CHARACTERISTICS

+

++

+ The specific numerical ratings applicable to the product

++ If applicable, the statement "In test of 30 min duration, the flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners, with no evidence of significant progressive combustion" (or the abbreviation "30 min.")

or

FR-S PLYWOOD*

+

* Applicable only to treated plywood having flame-spread and smoke-developed values of not more than 25

+ The statement "In test of 30 min duration, the flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners, with no evidence of significant progressive combustion" (or the abbreviation "30 min.")

Any of this information may be imprinted on the plywood or may be on separable paper labels, depending on factory production methods.

Alternate UL Mark

The Classification Mark of UL on the product is the only method provided by UL to identify products manufactured under its Classification and Follow-Up Service. The Classification Mark for these products includes the UL symbol, the word "CLASSIFIED" above the UL symbol (as illustrated in the Introduction of this Directory) or the statement "UND. LAB. INC. CLASSIFIED," the product identity "TREATED PLYWOOD," a control number, and the statement "SURFACE BURNING CHARACTERISTICS" or "FR-S PLYWOOD."

The Classification Mark with the statement "SURFACE BURNING CHARACTERISTICS" will include the specific numerical ratings applicable to the product, and if so qualified, the added statement "In test of 30 min duration, the flame spread did not progress more than ten and one-half (10-1/2) ft beyond the center line of the burners, with no evidence of significant progressive combustion" (or the abbreviation "30 min").

Classification Marks with the statement "FR-S PLYWOOD" are applicable to treated plywood having numerical ratings not more than 25 for flame spread and smoke developed, and also eligible for the "30 min test" statement quoted above.

Any of these Classification Mark texts may be imprinted on the plywood or may be separable paper Classification Marks depending on factory production methods.

* * * * *

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

Last Updated on 2013-05-16

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Reprinted from the Online Certifications Directory with permission from UL

© 2020 UL LLC

Access BUGV.R7003 on UL Product IQ: <https://iq.ulprospector.com/en/profile?e=13565>
(Free UL account registration required)